

DERALUNOX

ALUMINIUM AND
STAINLESS DEOXIDIZER



Industry

Construction

Automotive Industry

Environment

Hotels and Restaurants

Agriculture

FEATURES

Clear liquid of acid chemical reaction, without coloring.

PROPERTIES

DERALUNOX is miscible in water in all proportions, has a low surface tension, ensures a perfect penetration in encrusted dirtiness.

APPLICATION

Wet slightly and uniformly the surfaces to be cleaned.

Apply DERALUNOX diluted with cold water with a concentration in accordance with the thickness of the dirt to be cleaned, usually a dilution range from 1 litre per 2 to 3 litres of water for descaling operations or renewal, and 1 litre to 8 to 10 litres of water for frequent cleaning.

DERALUNOX is applied by spraying or brushing always from top to bottom.

Allow to react for 5 minutes and then wash with water, preferably under pressure always from top to bottom.

DERALUNOX is a product of acid character, in the case of exterior cleaning materials transportation or agri-food industry after the final cleaning and until neutralization of surfaces, the operation is finished by washing with a detergent compatible with food industry followed by a washing with potable water.

UTILIZATION

DERALUNOX is used for renovation and descaling of rolling equipment, such as road and rail cisterns, fixed tanks, cleaning and renewal of containers.

DERALUNOX is used in transport companies, agro-food, highways, factories, ports, shipyards, etc. ...

DERALUNOX descales and renews the rims of rolling equipment particularly oxidized.

With DERALUNOX you will get a renewed surface with a shiny appearance.

ADVANTAGES

- Renovation and descaling of surfaces
- Product of acid character
- Low surface tension
- Excellent performance in stainless steel and aluminum



DERALUNOX application example

TECHNICAL SPECIFICATIONS	
DILUTION	1 litre until 10 litres of water
CHEMICAL NATURE	Mineral acids, surfactants and hydro solvents
SURFACTANTS	Nonionic
PHYSICAL STATE / COLOUR	Colourless liquid
ODOUR	Slight acid
PH	0,50
SOLUBILITY IN WATER	Complete
CLEANING PERFORMANCE	Very good
RINSING	Yes
FOAMING	No
RELATIVE DENSITY	1,080
FLASH POINT	Not concerned
CHEMICAL REACTION	Acid
CLASSIFICATION	Corrosive
EXPIRATION	2 years. Stored in the original packaging. Protect from excessive sunlight. Avoid extreme temperatures.

APPLICATION MODE	DILUTION	RINSING
Spraying, brush (always from bottom to top), immersion or bathing	1 liter to 10 liters of cold water depending on the nature of dirtiness	Wash with water, preferably under pressure always from top to bottom.



CAUTIONS

Chemical product: Always read the label before using. Close the packing after each use. Keep out of children reach.

Avoid contact with the skin. In case of contact with skin or eyes, rinse with plenty of water. Do not mix with other products. Protect from cold. Do not use on anodized aluminum, lightweight, galvanized alloys, etc.

Always make a test to determine the compatibility and the appropriate contact time.



PORTUGAL

Imporquímica- Indústria Portuguesa de Produção Química, S.A.
Zona Industrial Alto do Carvalhinho, Lote 11 - Apartado 39
2861-909 Moita - Portugal
Tel: +351 212 808 390 | Fax: +351 212 808 395
E-mail: info@imporquimica.pt

ANGOLA

Imporquímica Angola, SA.
Estrada do Zango/Viana Polo Industrial Tubogás
Armazéns 35 e 36 - Município de Viana, Luanda Angola
Tel.: +244 222 290 850 | Fax: +244 222 290 230
E-mail: angola@imporquimica.com

CAPE VERDE

Imporquímica Cabo Verde, Lda.
Armazém Achada Grande de Trás
Ilha de Santiago, Praia - Cabo Verde
Tel.: +238 939 07 48
E-mail: caboverde@imporquimica.com

MOZAMBIQUE

Imporquímica Moçambique, Lda.
Avenida Zedequias Manganhela, n.º 267, Prédio JAT IV
4º andar, Maputo - Moçambique
Tel.: +258 845 797 467
E-mail: mocambique@imporquimica.com

NIGERIA

Imporquímica Nigeria Chemicals, Ltd.
Plot 59 Trans Amadi Industrial Layout,
Port Harcourt, Rivers State, Nigeria
Tel: +234 (0) 84 556 004
E-mail: info@nigeria-chemicals.com



visit us
IMPORQUIMICA.COM

DERALUNOX