

DESCOMAD

WOOD AND METAL
PANELS RELEASE AGENT

Construction

Industry

Institutional



FEATURES

Soluble oil.

PROPERTIES

DESCOMAD is easily emulsifiable with water, to guarantee the preservation of wood and metal formwork.

APPLICATION

DESCOMAD is used diluted in a proportion of 1 litre until 15 litres of water.

Further dilutions that are not represented here, it will be necessary to conduct tests to verify the exact concentration to use.

For an effective emulsion join the product with water.

Its application can be made by spraying, brush or other mechanical way. 1 liter of emulsion covers approximately 20 m².

UTILIZATION

DESCOMAD is used throughout the construction industry and public works and the application can be made either in metal formwork as wooden formwork.

UTILIZATION

DESCOMAD is a product that is not classified as flammable, which in itself is already a strong argument, because it will reduce the amount of flammable products on construction or in a warehouse.

The fact that it is a vegetable oil and not be based petroleum components, is the ideal product for companies that have or intend to have environmental certification.

ADVANTAGES

- Soluble oil
- It is easily emulsified in water
- Use in metal formwork and wood



DESCOMAD application example

TECHNICAL SPECIFICATIONS	
DILUTION	1 litre until 15 litres of water
CHEMICAL NATURE	Special oils
SURFACTANTS	Not applicable
PHYSICAL STATE / COLOUR	Brown liquid
ODOUR	Menthol
PH	Not applicable
SOLUBILITY IN WATER	Complete
CLEANING PERFORMANCE	Not applicable
RINSING	No
FOAMING	No
RELATIVE DENSITY	890 g/l
FLASH POINT	> 120°C
CHEMICAL REACTION	Alkaline
CLASSIFICATION	Not applicable
EXPIRATION	2 years. Stored in the original packaging. Protect from excessive sunlight. Avoid extreme temperatures.
APPLICATION MODE	DILUTION
Spraying, brush any other mechanical way.	1 litre until 15 litres of water



CAUTIONS

Chemical product: Always read the label before using. Close the packing after each use. Keep out of children reach.

Always make a test to determine the compatibility and the appropriate contact time.



PORTUGAL

Imporquímica- Indústria Portuguesa de Produção Química, S.A.
Zona Industrial Alto do Carvalhinho, Lote 11 - Apartado 39
2861-909 Moita - Portugal
Tel: +351 212 808 390 | Fax: +351 212 808 395
E-mail: info@imporquimica.pt

ANGOLA

Imporquímica Angola, SA.
Estrada do Zango/Viana Polo Industrial Tubogás
Armazéns 35 e 36 - Município de Viana, Luanda Angola
Tel.: +244 222 290 850 | Fax: +244 222 290 230
E-mail: angola@imporquimica.com

CAPE VERDE

Imporquímica Cabo Verde, Lda.
Armazém Achada Grande de Trás
Ilha de Santiago, Praia - Cabo Verde
Tel.: +238 939 07 48
E-mail: caboverde@imporquimica.com

MOZAMBIQUE

Imporquímica Moçambique, Lda.
Avenida Zedequias Manganhela, n.º 267, Prédio JAT IV
4º andar, Maputo - Moçambique
Tel.: +258 845 797 467
E-mail: mocambique@imporquimica.com

NIGERIA

Imporquímica Nigeria Chemicals, Ltd.
Plot 59 Trans Amadi Industrial Layout,
Port Harcourt, Rivers State, Nigeria
Tel: +234 (0) 84 556 004
E-mail: info@nigeria-chemicals.com



visit us
IMPORQUIMICA.COM

DESCOMAD